





/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-80	V
Collector to Emitter Voltage	V_{CEO}	-80	V
Emitter to Base Voltage	V_{EBO}	-5	V
Collector Current - Continuous	I_C	-500	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	


/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C = -50\mu A$	-80			V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C = -2mA$	-80			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E = -50\mu A$	-5			V
Collector Base Cut-Off Current	I_{CBO}	$V_{CB} = -50V$ $I_E = 0$			-0.5	μA
Collector Emitter Cut-Off Current	I_{CEO}	$V_{CE} = -65V$ $I_B = 0$			-5	μA
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB} = -4.0V$ $I_C = 0$			-0.5	μA
DC Current Gain	h_{FE}	$V_{CE} = -3.0V$ $I_C = -100mA$	120		390	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -500mA$ $I_B = -50mA$			-0.5	V
Transition Frequency	f_T	$I_C = -50mA$ $f = 100MHz$ $V_{CE} = -10V$		180		MHz
Collector output capacitance	C_{ob}	$V_{CB} = -10V$ $I_E = 0$ $f = 1.0MHz$		11		pF

/ Electrical Characteristic Curve




/ Package Dimensions



Dimensions in Millimeters		Dimensions in Inches	
	mm		in
L	2.82	2.02	0.79
B	1.50	1.70	0.06
C	0.50	0.30	0.01
E	2.50	3.00	0.10
F	1.00	2.00	0.04

/ Marking Instructions



T

DK

U h_{FE}


Note:

Q: Automobile halogen-free product Code

AK: Product Type Code

R: h_{FE} Classifications Symbol Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT23-3	3,000	10	30,000	4	120,000	7 ×8	210×205×205	445×230×435

/ Notices