

/ Descriptions

VRW056 QSQ Silicon NPN transistor in a SOT-23 Plastic Package.


/ Features

DHF0T434
High voltage, high current, high h_{FE} , low noise, excellent h_{FE} linearity, Qualified to AEC-Q101 Standards for High Reliability, HF Product.


/ Applications

Audio frequency general purpose amplifier applications, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	O	Y	GR	BL
h_{FE} Range	70~140	120~240	200~400	350~700
Marking	QLO	QLY	QLG	QLL


/ Absolute Maximum Ratings($T_a=25^\circ\text{C}$)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current	I_C	150	mA
Base Current	I_B	30	mA
Collector Power Dissipation	P_C	150	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55~150	


/ Electrical Characteristics($T_a=25^\circ\text{C}$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	$V_{CB}=60V$ $I_E=0$			0.1	A
Emitter Base Cut-Off Current	I_{EBO}	$V_{EB}=5.0V$ $I_C=0$			0.1	A
DC Current Gain	h_{FE}	$V_{CE}=6.0V$ $I_C=2.0mA$	70		700	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=100mA$ $I_B=10mA$		0.1	0.25	V
Transition Frequency	f_T	$V_{CE}=10V$ $I_C=1.0mA$	80			MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10V$ $I_E=0$ $f=1.0MHz$		2.0	3.5	pF
Noise Figure	NF	$V_{CE}=6.0V$ $I_C=0.1mA$ $R_g=10K$ $f=1.0KHz$		1.0	10	dB

/ Electrical Characteristic Curve



/ Marking Instructions



T

0

R h_{FE}

Note:

T: Dxwr p relh kdor j hq0iuhh surgxfw Fr gh

0 Product Type Code

R h_{FE} Classifications Symbol

() /

Note:

- 1

150 200%

60 120sec;

1.Preheating:150~200%, Time:60~120sec.
- 2

255[±]5%

5[±]0.5sec;

2.Peak Temp.:255[±]5%, Duration:5[±]0.5sec.
- 3

2 10%/sec.

3.Cooling Speed: 2~10%/sec.

/ Resistance to Soldering Heat Test Conditions

260[±]5%

10[±]1 sec.

Temp.:260±5

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units	Dimension	(unit mm ³)
--------------	-------	-----------	-------------------------