

/ Descriptions

SOT-89

Low dropout linear regulator in a SOT-89 Plastic Package .

/ Features

24V

1.5 μ A


$\pm 2\%$

Low power consumption,Low voltage drop,Small temperature drift coefficient,High input voltage up to 24V,The static current 1.5 μ A,The output voltage accuracy: $\pm 2\%$,HF Product.


/ Applications

For use in power equipment,Communication equipment,Audio and video equipment.

/ Equivalent Circuit



/ Pinning



PIN1 GND PIN 2 VIN PIN 3 VOUT

/ Marking

See Marking Instructions.

BRCO7550MT

Rev.B Jul.-2024




DATA SHEET


Parameter	Symbol	Rating	Unit
Working Voltage	V_{IN}	-0.3~+24	V
Thermal Resistance	$R_{\theta JA}$	200	/W
Power Consumption	P_D		

/ Typical Application Circuit


/ Basic Application



/ High Output Current Voltage Regulator




/ Short-Circuit Protection




/ Typical Application Circuit


/ Circuit for Increasing Output Voltage



/ Constant Current Regulator




/ Double Output Circuit





/ Marking Instructions



7550M


**

Note:

7550M: Product Type Code

** : Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
SOT-89	1,000	10	10,000	4	40,000	7" ×12	210×205×205	445×435×230

/ Notices