

BRCS030N10SHBD

Rev.A Sep.-2022

/ Descriptions


TO-263 N
N-CHANNEL MOSFET in a TO-263 Plastic Package.

/ Features


/ Applications

High frequency switching and synchronous rectification,BMS,Motor.

/ Equivalent Circuit



/ Pinning



PIN1 G PIN 2 4 D PIN 3 S

/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DSS}	100	V
Drain Current		$I_D(T_C=25^{\circ}C)$	212	A
Pulsed Drain Current		I_{DM}	445	A
Gate-Source Voltage		V_{GS}	± 20	V
Single Pulsed Avalanche Energy(L=0.5mH)		E_{AS}	1000	mJ
Avalanche Current		I_{AS}	50	A
Total Power Dissipation		$P_D(T_C=25^{\circ}C)$	260	W
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	
Thermal Resistance-Junction to Ambient	$t \leq 10s$	$R_{\theta JA}$	13	/W
	Steady-State		58	
Thermal Resistance-Junction to Case	Steady-State	$R_{\theta JC}$	0.48	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$	$I_D=250\mu A$	100	109		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V$	$V_{GS}=0V$			1	μA
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$	$V_{DS}=0V$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$	$I_D=250\mu A$	2	3	4	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$	$I_D=20A$		2.8	3.2	m Ω
	$R_{DS(on)}$	$V_{GS}=6V$	$I_D=10A$		3.8	5.5	
Forward On Voltage	V_{SD}	$V_{GS}=0V$	$I_S=1A$			1.2	V
Gate resistance	R_g	$f=1MHz$			1.3		Ω
Input Capacitance	C_{iss}	$V_{DS}=25V$ $f=1MHz$	$V_{GS}=0V$		9180		pF
Output Capacitance	C_{oss}				3240		
Reverse Transfer Capacitance	C_{rss}				305		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V,$ $I_D=20A$	$V_{DS}=50V,$		76		nC
Gate Source Charge	Q_{gs}				20		
Gate Drain Charge	Q_{gd}				12		

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=50V$ $R_L=2.5\Omega$ $R_{GEN}=3\Omega$		23		ns
Turn-On Rise Time	t_r			17		
Turn-Off Delay Time	$t_{d(off)}$			50		
Turn-Off Fall Time	t_f			21		

/ Electrical Characteristic Curve




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 6: Body-Diode Characteristics








Figure 5: On-Resistance vs. Gate-Source Voltage

/ Electrical Characteristic Curve




/ Package Dimensions



单位: mm

Symbol	Dimensions in Millimeters		Symbol	Dimensions in Millimeters	
	Min	Max		Min	Max
A	4.30	4.70	F _L	0.00	0.05
b	1.00	1.40	e1	2.34	2.74
b	0.70	0.90	e2	4.88	5.28
b1	1.15	1.35	L	15.00	16.00

/ Marking Instructions




Note:

BR: Company Code

030N10SH: Product Type

****: Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245 | 5 | 5 | 0.5sec; | 2.Peak Temp.:245 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-263	800	1	800	6	4,800	13" ×24	360×360×50	380×335×366

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-263	50	20	1,000	5	5,000	532×33×7.0	555×164×50	575×290×180

/ Notices