

/ Revised record

A	2021.03.24	All	AOS-AON6426		
B	2021.05.26	2	PK6B2BA ID PD Rth		

/ Descriptions

PDFN5*6 N
N-Channel MOSFET in a PDFN5*6 Plastic Package .


/ Features

Low $R_{DS(ON)}$ to minimize conductive loss;low Gate Charge for fast switching;Low Thermal resistance.


/ Applications

Battery Management

/ Equivalent Circuit




/ Pinning



PIN1、 2、 3: S

PIN4: G



PIN5、 6、 7、 8: D

Pin	极性
1	S
2	S
3	S
4	G
5	D
6	D
7	D
8	D

/ h_{FE} Classifications & Marking



。 See Marking Instructions.

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	30	V
Drain Current - Continuous		I_D	45	A
Drain Current – Pulsed		I_{DM}	135	A
Gate-Source Voltage		V_{GS}	± 20	V
Power Dissipation		$P_D(T_c=25^\circ\text{C})$	28	W
Single Pulse Avalanche Energy(L=0.5mH)		E_{AS}	211	mJ
Avalanche Current(L=0.5mH)		I_{AS}	23	A
Junction and Storage Temperature Range		T_j, T_{stg}	-55 to 150	$^\circ\text{C}$
Thermal resistance, junction - ambient	$t \leq 10\text{s}$	$R_{\theta JA}$	36	$^\circ\text{C/W}$
	Steady-State		64.8	
Thermal resistance, junction - case	Steady-State	$R_{\theta JC}$	4.5	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{D(on)}$	$V_{GS}=10V, V_{DS}=15V,$ $R_L=0.75\Omega, R_{GEN}=3\Omega$		8.1		ns
Turn-On Rise Time	t_r			8.6		
Turn-Off Delay Time	$t_{D(off)}$			29		
Turn-Off Fall Time	t_f			8		


/ Electrical Characteristic Curve



/ Electrical Characteristic Curve



/ Marking Instructions



说明：

BR： 为公司代码


060N03： 为为产品型号

Note：

BR： Company Code

060N03： Product Type.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|----|-----------|--|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180°C, Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5°C, Duration:5±0.5sec. |
| 3 | | | 2 | 10°C/sec. | 3. Cooling Speed: 2~10°C/sec. |

/ Resistance to Soldering Heat Test Conditions

260±5°C

10±1 sec.

Temp.:260±5°C

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
PDFN5*6	5000	2	10000	6	60000	13"×12	360×360×50	380×335×366

/ Notices