

Glass Passivated Bridge Rectifiers, Reverse Voltage:50~1000V,Forward Current:8.0A,GBJ package.



PCB

UL

94V-0

Ideal for printed circuit board, Case material molded plastic, The plastic material has U/L flammability classification 94V-0. Halogen free product.

General purpose.



1 2 3 4

PIN1 DC+ PIN2 AC PIN 3 AC PIN 4 DC-

See Marking Instructions

Parameter	Symbol	Rating							Unit
		GBJ 8005G	GBJ 801G	GBJ 802G	GBJ 804G	GBJ 806G	GBJ 808G	GBJ 810G	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current (with heatsink Note 2)	$I_{F(AV)}$	8.0							A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	I_{FSM}	200							A
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t	166							A ² s
Typical Junction Capacitance per element (Note1)	CJ	66							pF
Typical Thermal Resistance (Note2)	$R_{\theta Jc}$	1.6							/W
Operation Temperature Range	T_j	-55 to +150							
Storage Temperature Range	T_{stg}	-55 to +150							

NOTE:

1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2.Device mounted on 150mm*150mm*1.6mm Cu Plate Heatsink.



Parameter

Symbol

Test Conditions

Rating

04 212.9406.【Rati



G.4-TYPICAL FORWARD CHARACTERISTICS






FIG.3-TYPICAL JUNCTION CAPACITANCE




FI




REVERSE VOLTAGE,(VOLTS)



CD I Deckage Outline Dimensions






GBJ8005G:

****:

Product Type.

Lot No. Code, code change with Lot No.



Note:

- | | | | | | |
|---|-----|-----|----|------------|--|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 °C , Time:60~90sec. |
| 2 | 255 | 5 | 5 | 0.5sec; | 2.Peak Temp.:255 ± 5 °C , Duration:5 ± 0.5sec. |
| 3 | | | 2 | 10 °C/sec. | 3. Cooling Speed: 2~10 °C/sec. |

270 ± 5	10 ± 1 sec.	Temp.:270±5	Time:10±1 sec
---------	-------------	-------------	---------------

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
GBJ	-	-						