

/ Descriptions

SOT-23

NPN

Silicon NPN transistor in a SOT-23 Plastic Package.



/ Features

High current gain, low noise figure, high power gain.

/ Applications

2.5GHz

Amplifiers for operation up to 2.5GHz applications.

/ Equivalent Circuit**/ Pinning**

PIN1 Base

PIN 2 Emitter

PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Range	50~200
Marking	H7A

MMBR901LT1


Rev.F Apr.-2017

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	25	V
Collector to Emitter Voltage	V_{CEO}	15	V
Emitter to Base Voltage	V_{EBO}	2	V
Collector Current	I_C	30	mA
Collector Power Dissipation	P_C	300	mW
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{stg}	-55~150	°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	I				




/ Electrical Characteristic Curve




/ Package Dimensions

SOT-23

单位：mm



/ Marking Instructions



H


7A

Note:

H Company Code

7A Product Type

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5℃ Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱
						"		