

Rev.F May.-2019

50V~1000V 2.0A SMAF

Surface Mount Ultrafast Recovery Rectifier, Reverse Voltage: 50 to 1000V, Forward Current: 2.0A, SMAF thin package.


RoHS 2011/65/EU

Glass Passivated Chip Junction High efficiency Lead free in comply with EU RoHS 2011/65/EU directives For surface mounted applications. Halogen free product.

General purpose.



PIN	DESCRIPTION
1	Cathode
2	Anode




See Marking Instructions.

Parameter	Symbol	Rating							Unit
		US2AF	US2BF	US2DF	US2GF	US2JF	US2KF	US2MF	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_a = 65$	$I_{F AV}$	2.0							A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	50							A
Typical Thermal Resistance ¹⁾	R_{JA}	75							/W
Operating and Storage Temperature Range	T_j, T_{stg}	-55~+150							


Note:

1) P.C.B. mounted with 0.2 X 0.2" (5 X 5 mm) copper pad areass .

Parameter	Symbol	Test condition	Rating							Unit
			US2AF	US2BF	US2DF	US2GF	US2JF	US2KF	US2MF	
Maximum Instantaneous Forward Voltage	V _F	I _F =2.0A	1.0			1.3	1.65			V
Maximum DC Reverse Current at Maximum DC Blocking Voltage	I _R	T _a =25	5.0							uA
		T _a =125	100							
Maximum Reverse Recovery Time	T _{rr}	I _F =0.5A I _R =1.0A I _{rr} =0.25A	50				75			ns




Rev.F May.-2019



Marking

Type number	Marking code
US2AF	US2A
US2BF	US2B
US2DF	US2D
US2GF	US2G
US2JF	US2J
US2KF	US2K



US2A


1

3

Note:

US2A Product Type Code

Lot No. Code The 1st means:YM Code The last 3 means:little Lot No
Code



- Note:

1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.

2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱
SMAF	3000	5	15000	5	75000	7 ×11	185X180X105	390X385X205